

INMAC -- INMAC ANTI-STATIC SPRAY -- 6850-00F000367

=====
Product Identification
=====

Product ID:INMAC ANTI-STATIC SPRAY
MSDS Date:01/01/1985
FSC:6850
NIIN:00F000367
MSDS Number: BBGLV
=== Responsible Party ===
Company Name:INMAC
CAGE:3T092
=== Contractor Identification ===
Company Name:INMAC
CAGE:3T092

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)
CAS:71-55-6
RTECS #:KJ2975000
Fraction by Wt: 50%
OSHA PEL:350 PPM/450 STEL
ACGIH TLV:350 PPM/450 STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS
Ozone Depleting Chemical:1

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 50%
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500 STEL;9192

Ingred Name:CARBON DIOXIDE
CAS:124-38-9
RTECS #:FF6400000
Fraction by Wt: 5%
OSHA PEL:5000 PPM
ACGIH TLV:5000PPM/30000STEL;93

=====
Hazards Identification
=====

Effects of Overexposure:EXCESSIVE INHALATION MAY CAUSE NASAL
IRRITATION. EYES MAY BE PAINFUL FOR A TIME AFTER RINSING OUT.

=====
First Aid Measures
=====

First Aid:IF UNCONSCIOUS, REMOVE VICTIM TO FRESH AIR AND CALL A
PHYSICIAN. EYES: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER. IF
UNCONSCIOUS FROM INHALATION DO NOT GIVE ADRENALINE-TYPE DRUGS. THIS
EFFECT WOULD ONLY OCCUR IN CASES OF EXTREME INHALATION.

=====
Fire Fighting Measures
=====

Extinguishing Media:WATER FOG, DRY CHEMICAL, CARBON DIOXIDE, ALCOHOL
FOAM
Fire Fighting Procedures:USE SHIELDING TO PROTECT AGAINST BURSTING
CONTAINERS.
Unusual Fire/Explosion Hazard:AT ELEVATED TEMPERATURES(>130F)
CONTAINERS MAY VENT, RUPTURE, OR BURST.

=====
Accidental Release Measures
=====

Spill Release Procedures:AVOID BREATHING VAPORS, AVOID SKIN CONTACT
WITH LIQUID. REMOVE IGNITION SOURCES. SOAP WITH ABSORBENT MATERIAL
AND DISPOSE OF AS WITH OIL- OR GASOLINE-SOAKERAGS.

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT STORE WHERE TEMPERATURES EXCEED
54'C, 130'F.
Other Precautions:PLEASE READ AND FOLLOW DIRECTIONS ON PRODUCT LABEL;
THEY ARE YOUR BEST GUIDE TO USING THIS PRODUCT IN THE MOST
EFFECTIVE WAY AND GIVE NECESSARY PRECAUTIONS TO PROTECT YOUR HEALTH.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:MASK MAY BE WORN FOR PROLONGED OR HEAVY SPRAYING
Ventilation:MECHANICAL (GENERAL AREA) SHOULD BE ON WHILE SPRAYING
Protective Gloves:RUBBER, POLYETH
Eye Protection:DO NOT SPRAY TOWARD EYES
Other Protective Equipment:DO NOT WEAR CLOTHING SOAKED BY SPRAY.
Supplemental Safety and Health
2465 AUGUSTINE DRIVE, P.O. BOX 4780, SANTA CLARA, CA

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:N.A.
Vapor Density:>1
Spec Gravity:N.A.
Evaporation Rate & Reference:N.A.
Solubility in Water:1-10%
Appearance and Odor:SOLID CONE WET MIST; CHLOR. SOLVENT ODOR
Percent Volatiles by Volume:99

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE WITH COMMON MATERIALS
Hazardous Decomposition Products:CARBON MONOXIDE, PHOSGENE,
HYDROCHLORIC ACID.

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT PUNCTURE OR INCINERATE CONTAINERS. GIVE
EMPTY, LEAKING OR FULL CONTAINERS TO A DISPOSAL SERVICE EQUIPPED TO
SAFELY HANDLE AND DISPOSE OF PRESSURIZED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.